


Air or Nitrogen Hurricane Boosters



**Models: B18-62
B18-63**



Hurricane boosters are second-to-none. They are smaller, lighter and still pack as much power as the larger and heavier comparable units available in the marketplace today.

Our quality control and turnkey manufacturing process guarantee excellence, while superior engineering and design help drive custom solutions for our customers. Every feature that is built into our boosters shows you the experience, the power, the quality... *the Hurricane difference.*

Over 40 years of experience has taught us to maximize every component. Like all of our boosters, this unit provides you with a better penetration rate, cooler bit temperatures and longer bit life.

Typical applications include: coal bed methane, oil and gas air/foam drilling, nitrogen generation, and pipeline services.

Sustainable Productivity

Atlas Copco

Specifications

Booster	B18-62/2175		B18-63/3000
Booster type	Model 855 6 cylinders, reciprocating		
Drive engine	Caterpillar C18 630 bhp @ 1800 rpm		
Booster stages	1 stage	2 stage	3
Max suction pressure (psi / bar)	350 / 24		325 / 22
Max discharge pressure (psi / bar)	800 / 55	2175 / 150	3000 / 207
Capacity at max suction pressure (cfm / m ³ /min)	3600 / 102	2700 / 76.5	1900 / 54
Booster oil capacity (gal / l)	10 / 38		
Engine oil capacity (gal / l)	10 / 38		
Fuel tank capacity (gal / l)	162 / 613		
Max operating ambient temperature (°F / °C)	125 / 52		
Wet weight (lb / kg)	18,400 / 8,346		
Overall dimensions, L x W x H (in / cm)	216 x 87 x 87.5 / 549 x 221 x 222		
Suction connection	4" npt		3" npt
Discharge connection	3" npt		1 1/2" npt

Standard Features

- Automatic load/unload system
- On board fuel tank
- Booster bypass manifold (single and 2-stage only)
- Engine speed adjustment
- Double acting concentric valves
- Staging valves on the 2-stage models
- Watercooled booster block and valves
- Precooler (a+15°F / 8°C) & suction scrubber tank
- Aftercooler (a+50°F / 28°C)
- Low pressure switch at booster inlet
- Open skid with four point lifting
- 24 volt DC starting and operating system
- Suction, interstage and discharge safety relief valves
- Full function instrument panel monitoring all pressures, temperatures and controls with full protection shutdown and fault indicators



Options

- Digital control panel
- Automatic scrubber drain valve
- Cold weather kit
- Manual louvers in front of coolers
- Airstarter
- Spark arrestor
- Overspeed shutdown valve
- Inlet particle filter
- Lights for night operation
- Service packs 250/500/1000/2000 hours
- Valve and piston kits

Containerized and rig safe models as well as other options, capacities and pressures are available upon request.



Atlas Copco

Never use compressed air as breathing air without prior purification in accordance with local legislation and standards.

Atlas Copco Hurricane LLC
Part of the Atlas Copco Group
Phone: (800) 754-7408, +1 (317) 736-3800
www.atlascopco.com/hurricane